

Technical Bulletin # 470

Epoxy repair and patching compound

Product Description

PHILLYBOND #6 is a two-component, high strength epoxy paste for the repair of punctures or cracks in tanks, pumps, pipes, steam lines, sea chests, valve bodies, etc. The material is also used to fill holes, voids and to provide a smooth surface for repairs [at temperatures up to 428°F (220°C)], PHILLYBOND #6 is resistant to most acids, alkali and hydrocarbons and will adhere to clean surfaces such as steel, cast iron, bronze, aluminum, copper, nickel, wood and most plastics.

Surface Preparation

Repair surfaces must be clean and sound and free of oil, dirt, old paint and other foreign matter. Blast, abrade or clean surface with emery cloth to rough bright finish for best adhesion. Final rinse of surface with Impax IXT 59 solvent helps to ensure complete removal of grease and oils.

Mixing and Application Instructions

Mix white resin with black hardener - four parts resin to one part hardener by weight or volume - with putty knife or similar tool until a streak-free uniform color is achieved. As PHILLYBOND #6 is a fast curing system, mix only that amount that can be used in 10-15 minutes. Apply the mixed compound to the repair area forming a cross section of at least 3/8" (9.5mm) thick. The patch should extend at least 2" (5cm) on all sides of the damaged area. PHILLYBOND #6 may be smoothed by wetting putty knife with IXT 59 solvent or water. After hardening PHILLYBOND #6 can be machined or sanded, as desired, for a smoother surface.

Technical Information

| | |
|-------------------------|---|
| COLOR: | Gray (resin – white; hardener – black) |
| CURE TIME: | 1 hr @72 °F (22 °C) @ ½ " (12.7mm) thickness |
| MIXING RATIO: | 4:1 by volume and weight |
| PACKAGING: | 1 lb (454 grams) kit, 10 kits per case 1 gallon (3.785 liter)kit |
| POT LIFE: | 10 -15 minutes @72 °F (22 °C) |
| SHELF LIFE: | Two years/ Store in a cool dry area |
| TEMPERATURE RESISTANCE: | 428 °F (220 °C) |
| SHEAR STRENGTH: | 1000 psi (70.3 cm ² /kg) |
| VISCOSITY: | Paste putty |
| MIL SPEC: | R-17882-C |

Date

07/2006

General: Every reasonable effort is made to insure the technical information and recommendations on these data pages are true and accurate to the best of our knowledge at the date of issuance. However, this information is subject to change without notice. Prior versions of this publication are invalid with the release of this version. Products and information are intended for use by qualified applicators that have the required background, technical knowledge, and equipment to perform said tasks in a satisfactory manner. Consult your local distributor for product availability, additional product information, and technical support.

Warranty: ITW Polymer Technologies, a division of Illinois Tool Works Inc., warrants that its products meet their printed specifications. This is the sole warranty. This warranty expires one year after product shipment.

Warranty Claims: If any product fails to meet the above, ITW Polymer Technologies will, at its option, either replace the product or refund the purchase price. ITW Polymer Technologies will have no other liability for breach of warranty, negligence, or otherwise. All warranty claims must be made in writing within one year of the date of shipment. No other claims will be considered.

Disclaimer: ITW Polymer Technologies makes no other warranty, expressed or implied, and specifically disclaims any warranty of merchantability or fitness for a particular purpose.

Suggestions concerning the use of products are not warranties. The purchaser assumes the responsibility for determining suitability of products and appropriate use. ITW Polymer Technologies' sole liability, for breach of warranty, negligence or otherwise, shall be the replacement of product or refund of the purchase price, at ITW Polymer Technologies' election. Under no circumstances shall ITW Polymer Technologies be liable for any indirect, incidental or consequential damages.

Modification of Warranty: No distributor or sales representative has the authority to change the above provisions. No change in the above provisions will be valid unless in writing and signed by an officer or the Technical Director of ITW Polymer Technologies. No term of any purchase order shall serve to modify any provision of this document.

Mediation and Arbitration: If any dispute arises relating to products or product warranties, either the purchaser or ITW Polymer Technologies may a) initiate mediation under the then current Center for Public Resources (CPR) Model Procedure for Mediation of Business Disputes, or b) initiate a non-binding arbitration under the rules of the American Arbitration Association for the resolution of commercial disputes.

ITW POLYMER TECHNOLOGIES

130 Commerce Drive • Montgomeryville, PA 18936 • 215-855-8450 • Fax 215-855-4688
www.chockfast.com

