

PHILLYCLAD 1775/620TS HARDENER

Last revised: 05/07/01

Printed: 09/19/01

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical family Polyamines and modified polyamines

General information: The following data pertain to the hardener only; properly mixed and cured epoxies are not hazardous.

MANUFACTURER

ITW Philadelphia Resins
130 Commerce Dr.
Montgomeryville, PA 18936

EMERGENCY INFORMATION

Emergency telephone number
(CHEMTREC) (800) 424-9300
Other calls: (215) 855-8450

2. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS CONSTITUENTS	Constituent	Abbr.	CAS No.	Weight percent	Exposure limits		
					ACGIH TLV	OSHA PEL	Other Limits
	Tetraethylenepentamine	TEPA	112572	< 20	n/e	n/e	n/e
	2,4,6-Tris(Dimethylaminomethyl)phenol	DMP	90722	1-10	n/e	n/e	n/e
	Amidoamine		*	> 70	n/e	n/e	n/e

"TLV" means the Threshold Limit Value exposure (eight-hour, time-weighted average, unless otherwise noted) as established by the American Conference of Governmental Industrial Hygienists. "STEL" indicates a short-term exposure limit. "PEL" indicates the OSHA Permissible Exposure Limit. "n/e" indicates that no exposure limit has been established. An asterisk (*) indicates a substance whose identity is a trade secret of our supplier and unknown to us.

3. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance, physical form, odor: Amber liquid with mild ammonia-like odor.

WARNING! Eye, skin and respiratory irritant. Harmful if absorbed through skin. Potential skin sensitizer.**Potential health effects:****Primary routes of exposure:**

Skin contact Skin absorption Eye contact Inhalation Ingestion

Symptoms of acute overexposure:**Skin:**

Severe irritant.

Eyes:

Severe irritant. May cause permanent injury, including blindness.

Inhalation:

Irritation of nose and throat; nausea and vomiting in severe cases

Ingestion:

May cause irritation of mouth and throat and gastrointestinal tract.

Effects of chronic overexposure:

Repeated skin contact can cause sensitization, with itching, rashes, or swelling of the skin. May cause respiratory sensitization/asthmatic response. Prolonged or severe overexposure to DMP vapor can cause delayed lung damage and chemical pneumonia. Repeated and/or prolonged exposures may result in: adverse respiratory effects (such as

Medical conditions which may be aggravated by exposure: as conjunctivitis or corneal damage),

Asthma, chronic respiratory disease (e.g. bronchitis, emphysema), eye disease, skin disorders and allergies.

Carcinogenicity -- OSHA regulated: No **ACGIH:** No **National Toxicology Program:** No

International Agency for Research on Cancer: No

Cancer-suspect constituent(s): none

Other effects:

Product is absorbed through the skin and may cause nausea, headache and general discomfort.

4. FIRST AID MEASURES**First aid for eyes:**

Immediately flush with clean water for at least 15 minutes while gently holding eyelids open. Get medical help as soon as possible.

First aid for skin:

Immediately remove contaminated clothing and shoes and wash well with soap and warm water. See a doctor if irritation develops.

First aid for inhalation:

Remove patient to fresh air. Give oxygen or artificial respiration if needed. See a doctor if symptoms persist.

First aid for ingestion:

Do not induce vomiting. Dilute with lots of milk or water and get immediate medical help.

5. FIRE FIGHTING MEASURES**Extinguishing media:**
 Water

 Carbon dioxide

 Dry chemical

 Foam

 Alcohol foam

Flash Point (°F): >200

Method: TCC

Explosive limits in air -- Lower: n/d

Upper: n/d

Special firefighting procedures:

Firefighters should wear self-contained breathing apparatus and sufficient protective gear to prevent all skin and eye contact with this material.

Unusual fire and explosion hazards:

None

Hazardous products of combustion:

Acrid and toxic fumes with organic amines, ammonia, oxides of carbon and nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Spill control:

Avoid personal contact. Eliminate ignition sources. Ventilate area.

Cleanup:

For large spills, pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand, or other suitable material and dispose of properly. Flush area with water to remove trace residue.

Containment:

Dike, contain and absorb with clay, sand or other suitable material.

Special procedures:

Prevent spill from entering drainage/sewer systems, waterways, and surface waters.

7. HANDLING AND STORAGE

Handling precautions:

Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after using and particularly before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing and protective gear before reuse. Discard contaminated leather articles. Handle mixed resin and hardener in accordance with the potential hazard of the curing agent used. Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dusts, which includes crystalline silica, during sanding/grinding of cured product.

Storage precautions:

Store in a cool, dry area away from high temperatures and flames.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

Ventilation:

General mechanical ventilation is adequate for occasional use. For prolonged or repeated use, local exhaust is recommended.

Other engineering controls:

Have emergency shower and eye wash stations available.

Personal protective equipment

Eye and face protection:

Safety glasses with sideshields or chemical goggles.

Skin Protection:

Chemical-resistant rubber (neoprene, butyl rubber, polyvinyl chloride or nitrile) gloves and other protective gear as needed to prevent skin contact.

Respiratory protection:

None needed in normal use with proper ventilation. In poorly ventilated areas or when creating a dust or mist, use NIOSH-approved organic vapor respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific gravity:	0.95	Boiling point (°F):	>450
Melting point (°F):	n/d	Vapor density (air = 1):	>1
Vapor pressure (mmHg):	<0.01	at 68 °F	Evaporation rate (butyl acetate = 1): <<1
VOC (grams/liter):	0	Solubility in water:	n/d
Percent volatile by volume:	0	pH (5% solution or slurry in water):	Alkaline
Percent solids by weight:	100		0

10. STABILITY AND REACTIVITY

This product is chemically stable. Hazardous polymerization will not occur.

Conditions to avoid:

Extreme heat or open flame

Incompatible materials:

Mineral and organic acids, sodium or calcium hypochlorite, oxidizing agents, nitrous acid, nitrites, peroxides, nitrosating agents.

Hazardous decomposition products:

Acrid and toxic fumes with organic amines, ammonia, oxides of carbon and nitrogen

Conditions of hazardous polymerization:

Heat is released when this product is mixed with epoxy resins; use care when mixing large quantities.

11. TOXICOLOGICAL INFORMATION**Acute oral effects:**

LD50 (rat): > 2000 mg/kg (estimate)

No data.

Acute dermal effects

LD50 (rabbit): > 2000 mg/kg (estimate)

TETA has been found to be toxic by skin absorption (ANSI Z129.1 1988). TETA is a severe irritant to the skin of a rabbit.

Acute inhalation effects:

LC50 (rat): No data in 0 hours

No data.

Eye irritation:

TETA and DMP are severe irritants to the eyes of a rabbit.

Subchronic effects

No data.

Chronic effects

It has been generally observed in animal studies that aliphatic amines can cause changes in the lungs and heart. TETA has been found to produce liver and kidney damage and brain congestion in dermally exposed animals.

Carcinogenicity, teratogenicity, and mutagenicity:

TETA has shown activity in some in vitro genotoxicity tests, but is negative in in vivo test. Several developmental toxicity studies have reported that TETA can cause adverse embryofetal effects. These effects, however, are associated with only high maternally toxic dosages with induction of severe copper deficiency.

Toxicological information on hazardous chemical constituents of this product:

Constituent	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat, 4 hours)
Tetraethylenepentamine	3224 mg/kg	660 mg/kg	n/d

2,4,6-Tris(Dimethylaminomethyl)phenol	1670 mg/kg	1400 mg/kg	> 0.5 mg/L
Amidoamine	> 2000 mg/kg	> 2000 mg/kg	n/d

12. ECOLOGICAL INFORMATION

Ecotoxicity:

No data.

Mobility and persistence:

No data.

Environmental fate:

No data.

13. DISPOSAL CONSIDERATIONS

Waste management recommendations:

If this material becomes a waste, it would not be a hazardous waste by RCRA criteria (40CFR 261). Dispose of according to applicable federal, state, and local regulations.

14. TRANSPORT INFORMATION

Proper shipping name: Non-regulated

Technical name: N/A

Hazard class: N/A

UN number: N/A

Packing group: N/A

IMDG Page no.: N/A

Emergency Response Guide no.: N/A

Other: N/A

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA:

All ingredients of this product are listed, or are exempt from listing, on the TSCA Inventory.

The following RCRA code(s) applies to this material if it becomes waste: None

Regulatory status of hazardous chemical constituents of this product:

Constituent	Extremely Hazardous*	Toxic Chemical**	CERCLA RQ (lbs)	TSCA 12B Export Notification
Tetraethylenepentamine	No	No	No	Not required
2,4,6-Tris(Dimethylaminomethyl)phenol	No	No	No	Not required
Amidoamine	No	No	No	Not required

*Consult the appropriate regulations for emergency planning and release reporting requirements for substances on the SARA Section 301 Extremely Hazardous Substances list.

**Substances for which the "Toxic Chemical" column is marked "Yes" are on the SARA Section 313 list of Toxic Chemicals, for which release reporting may be required. Consult the appropriate regulations for specific requirements.

Classification of this material for SARA Section 312 hazardous materials inventory reporting:

Immediate health hazard Delayed health hazard

Canadian regulations

WHMIS hazard class(es): D2B

All components of this product are on the Domestic Substances List.

16. OTHER INFORMATION

Hazardous Materials Information System (HMIS) ratings:		
Health	Flammability	Reactivity
3*	1	1

The information and recommendations in this document are based on the best information available to us at the time of preparation, but we make no other warranty, express or implied, as to its correctness or completeness, or as to the results of reliance on this document.

PHILLYCLAD 1775/ 620TS RESIN

Last revised: 05/08/01

Printed: 09/19/01

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical family Epoxy resin

General information: This information applies to the resin component of the two-part kit; handle freshly-mixed resin and hardener as recommended for the hardener. After curing, the product is not hazardous.

MANUFACTURER

ITW Philadelphia Resins
130 Commerce Dr.
Montgomeryville, PA 18936

EMERGENCY INFORMATION

Emergency telephone number
(CHEMTREC) (800) 424-9300
Other calls: (215) 855-8450

2. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS CONSTITUENTS	Constituent	Abbr.	CAS No.	Weight percent	Exposure limits		
					ACGIH TLV	OSHA PEL	Other Limits
	Bisphenol A diglycidyl ether resin	DGEB PA	25068386		n/e	n/e	n/e

"TLV" means the Threshold Limit Value exposure (eight-hour, time-weighted average, unless otherwise noted) as established by the American Conference of Governmental Industrial Hygienists. "STEL" indicates a short-term exposure limit. "PEL" indicates the OSHA Permissible Exposure Limit. "n/e" indicates that no exposure limit has been established. An asterisk (*) indicates a substance whose identity is a trade secret of our supplier and unknown to us.

3. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance, physical form, odor: viscous liquid with little odor.

WARNING! Eye and skin irritant. Potential skin sensitizer.

Potential health effects:**Primary routes of exposure:**

Skin contact Skin absorption Eye contact Inhalation Ingestion

Symptoms of acute overexposure:**Skin:**

Moderate irritant. Contact at elevated temperatures can cause thermal burns. May cause skin sensitization (rashes, hives).

Eyes:

Moderate irritant. Contact at elevated temperatures can cause thermal burns.

Inhalation:

The low vapor pressure of the resin makes inhalation unlikely in normal use.

Ingestion:

Acute oral toxicity is low. May cause gastric distress.

Effects of chronic overexposure:

Prolonged or repeated skin contact may cause sensitization, with itching, swelling, or rashes on later exposure.

Medical conditions which may be aggravated by exposure:

Preexisting eye and skin disorders. Development of preexisting skin or lung allergy symptoms may increase.

Carcinogenicity -- OSHA regulated: No **ACGIH:** No **National Toxicology Program:** No

International Agency for Research on Cancer: No

Cancer-suspect constituent(s): None

Other effects:

See section 11.

4. FIRST AID MEASURES**First aid for eyes:**

Flush eye with clean water for at least 15 minutes while gently holding eyelids open. Get immediate medical attention.

First aid for skin:

Immediately remove contaminated clothing and excess contaminant. Flush skin with water. Wash thoroughly with soap and warm water. Consult a physician if irritation develops.

First aid for inhalation:

Remove patient to fresh air. Administer oxygen if breathing is difficult. Get medical attention if symptoms persist.

First aid for ingestion:

Do NOT induce vomiting. Give two glasses of water to dilute if patient is conscious. Get medical attention.

Note to physician:

In general, emesis induction is unnecessary in high viscosity, low volatility products, e.g., neat epoxy resins.

5. FIRE FIGHTING MEASURES**Extinguishing media:**

Water

Carbon dioxide

Dry chemical

Foam

Alcohol foam

Flash Point (°F): >400

Method: PMCC

Explosive limits in air -- Lower: n/d

Upper: n/d

Special firefighting procedures:

Material will not burn unless preheated. Do not enter confined space without full bunker gear. Firefighters should wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers with water.

Unusual fire and explosion hazards:

Heating above 300 deg F in the presence of air may cause slow oxidative decomposition and above 500 deg F may cause polymerization.

Hazardous products of combustion:

When heated to decomposition it emits fumes of Cl-, carbon monoxide, other fumes and vapors varying in composition and toxicity.

6. ACCIDENTAL RELEASE MEASURES

Spill control:

Avoid personal contact. Eliminate ignition sources. Ventilate area.

Cleanup:

For large spills, pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand, or other suitable material and dispose of properly. Flush area with water to remove trace residue.

Containment:

Dike, contain and absorb with clay, sand or other suitable material.

Special procedures:

Prevent spill from entering drainage/sewer systems, waterways, and surface waters.

7. HANDLING AND STORAGE

Handling precautions:

Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after using and particularly before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing and protective gear before reuse. Discard contaminated leather articles. Handle mixed resin and hardener in accordance with the potential hazard of the curing agent used. Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against nuisance dust during sanding/grinding of cured product.

Storage precautions:

Store in a cool, dry area away from high temperatures and flames.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

Ventilation:

Local exhaust ventilation is preferred although good general mechanical ventilation is usually adequate for most industrial applications. Local exhaust is recommended for confined areas.

Other engineering controls:

Have emergency shower and eye wash available.

Personal protective equipment

Eye and face protection:

Safety glasses with side shields.

Skin Protection:

Chemical-resistant gloves and other gear as required to prevent skin contact.

Respiratory protection:

None required at normal handling temperatures and conditions. Use NIOSH approved organic vapor cartridges for uncured resin and dust/particle respirators during grinding/sanding operations of cured resin as exposure levels dictate.

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific gravity:	1.19	Boiling point (°F):	>500
Melting point (°F):	n/d	Vapor density (air = 1):	>1
Vapor pressure (mmHg):	0.03 mm Hg at 171 °F	Evaporation rate (butyl acetate = 1):	<<1
VOC (grams/liter):	0	Solubility in water:	Negligible
Percent volatile by volume:	0	pH (5% solution or slurry in water):	neutral
Percent solids by weight:	100		0

10. STABILITY AND REACTIVITY

This product is chemically stable. Hazardous polymerization will not occur.

Conditions to avoid:

Open flame and extreme heat

Incompatible materials:

Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines).

Hazardous decomposition products:

Oxides of carbon; aldehydes, acids and other organic substances may be formed during combustion or elevated temperature (>500 deg F) degradation.

Conditions of hazardous polymerization:

Heat is generated when resin is mixed with curing agents; Run-a-way cure reactions may char and decompose the resin, generating unidentified fumes and vapors which may be toxic.

11. TOXICOLOGICAL INFORMATION**Acute oral effects:**

LD50 (rat): 11,400 mg/kg (DGE BPA Resin)

Acute dermal effects

LD50 (rabbit): >20 ml/kg (DGE BPA Resin)
DGE BPA: Draize -1.6 (rabbit)

Acute inhalation effects:

LC50 (rat): No deaths in saturated in 0 hours

Eye irritation:

DGE BPA: Draize -2 (rabbit)

Subchronic effects

No data available

Chronic effects

Prolonged or repeated skin contact may cause sensitization, with itching, swelling, or rashes on later exposure. Studies have shown bisphenol A diglycidyl ether resin to cause allergic contact dermatitis.

Carcinogenicity, teratogenicity, and mutagenicity:

1) MUTAGENICITY: Liquid resins based on diglycidyl ether of Bisphenol A (DGE BPA), have proved to be inactive when tested by in vivo mutagenicity assays. These resins have shown activity in in vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat liver cells. The significance of these tests to man is unknown. 2) CARCINOGENICITY: Recent 2-year bioassays in rats and mice exposed by the dermal route to DGE BPA yielded no evidence of carcinogenicity to the skin or any other organs. This study clarifies prior equivocal results from a 2-year mouse skin painting study, which were suggestive, but not conclusive, for weak carcinogenic activity. 3) The International Agency for Research on Cancer (IARC) concluded that DGE BPA is not classifiable as a carcinogen (IARC group 3), that is human and animal evidence of carcinogenicity is inadequate.

Toxicological information on hazardous chemical constituents of this product:

Constituent	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat, 4 hours)
Bisphenol A diglycidyl ether resin	11.4 g/kg	>20 ml/kg	no deaths

12. ECOLOGICAL INFORMATION**Ecotoxicity:**

No data available.

Mobility and persistence:

No data available.

Environmental fate:

No data available.

13. DISPOSAL CONSIDERATIONS**Waste management recommendations:**

If this resin becomes a waste, it would not be a hazardous waste by RCRA criteria (40CFR 261). Dispose of according to applicable federal, state, and local regulations.

14. TRANSPORT INFORMATION**Proper shipping name:** Non-regulated**Technical name:** N/A**Hazard class:** N/A**UN number:** N/A**Packing group:** N/A**IMDG Page no.:** N/A**Emergency Response Guide no.:** N/A**Other:****15. REGULATORY INFORMATION****U.S. Federal Regulations****TSCA:**

All ingredients of this product are listed, or are exempt from listing, on the TSCA Inventory.

The following RCRA code(s) applies to this material if it becomes waste: None

Regulatory status of hazardous chemical constituents of this product:

Constituent	Extremely Hazardous*	Toxic Chemical**	CERCLA RQ (lbs)	TSCA 12B Export Notification
Bisphenol A diglycidyl ether resin	No	No	No	Not required

*Consult the appropriate regulations for emergency planning and release reporting requirements for substances on the SARA Section 301 Extremely Hazardous Substances list.

**Substances for which the "Toxic Chemical" column is marked "Yes" are on the SARA Section 313 list of

Toxic Chemicals, for which release reporting may be required. Consult the appropriate regulations for specific requirements.

Classification of this material for SARA Section 312 hazardous materials inventory reporting:

Immediate health hazard Delayed health hazard

Canadian regulations**WHMIS hazard class(es):** D2B

All components of this product are on the Domestic Substances List.

16. OTHER INFORMATION

Hazardous Materials Information System (HMIS) ratings:		
Health	Flammability	Reactivity
2*	1	1

Revisions for this issue:**MSDS Section****Revisions**

3	Updated health data
11	Updated toxicology data

The information and recommendations in this document are based on the best information available to us at the time of preparation, but we make no other warranty, express or implied, as to its correctness or completeness, or as to the results of reliance on this document.